



双卡套直通接头



英制双卡套直通						
T-Tube o. D. (in.)	基本订购信息	尺寸mm				
		L	C	G	F	E
1/16	K1-US	25.1	8.6	7.9	11.1	1.3
1/8	K2-US	35.6	12.7	11.1	11.1	2.3
3/16	K3-US	37.3	13.7	12.7	12.7	3.0
1/4	K4-US	40.9	15.2	14.3	12.7	4.8
5/16	K5-US	42.9	16.2	15.9	14.3	6.4
3/8	K6-US	45.0	16.8	17.5	15.9	7.1
1/2	K8-US	51.3	22.9	22.2	20.6	10.4
5/8	K10-US	52.1	24.4	25.4	23.9	12.7
3/4	K12-US	53.6	24.4	28.6	27.0	15.7
7/8	K14-US	55.1	25.9	31.8	34.9	18.3
1	K16-US	64.8	31.2	38.1	34.9	22.4
1 1/8	K18-US	64.8	31.2	44.5	41.3	24.6
1 1/4	K20-US	92.2	41.1	47.6	44.5	27.7
1 1/2	K24-US	108	50.0	57.2	54.0	34.0


公制双卡套直通						
T-Tube o. D. (mm)	基本订购信息	尺寸mm				
		L	C	G	F	E
2	K02-US	35.6	12.9	12	12	1.7
3	K03-US	35.3	12.9	12	12	2.4
4	K04-US	37.3	13.7	12	12	2.4
6	K06-US	41.0	15.3	14	14	4.8
8	K08-US	43.2	16.2	16	15	6.4
10	K010-US	46.2	17.2	19	18	7.9
12	K012-US	51.2	22.8	22	22	9.5
14	K014-US	52.0	24.4	25	24	11.1
15	K015-US	52.0	24.4	25	24	11.9
16	K016-US	52.0	24.4	25	24	12.7
18	K018-US	53.5	24.4	30	27	15.1
20	K020-US	55.0	26.0	32	30	15.9
22	K022-US	55.0	26.0	32	30	18.3
25	K025-US	65.0	31.3	38	35	21.8
28	K028-US	85.0	36.6	46	41	21.8
30	K030-US	92.7	39.6	50	46	26.2
32	K032-US	97.3	42.0	50	46	28.6
38	K038-US	113.6	49.4	60	55	33.7

双卡套外螺纹直通接头




英制双卡套外螺纹直通接头			NPT 螺纹						
T-Tube O.D. (in.)	NPT 尺寸	基本订购信息	尺寸mm						
			L	B	C	E	G	F	
1/16	1/16	K1M1-US	23.9	9.7	8.6	1.3	7.9	7.9	
1/16	1/8	K1M2-US	26.2	9.7	8.6	1.3	7.9	11.1	
1/16	1/4	K1M4-US	31.0	14.2	8.6	1.3	7.9	14.3	
1/8	1/16	K2M1-US	29.7	9.7	12.7	2.3	11.1	11.1	
1/8	1/8	K2M2-US	30.5	9.7	12.7	2.3	11.1	11.1	
1/8	1/4	K2M4-US	35.6	14.2	12.7	2.3	11.1	14.3	
1/8	3/8	K2M6-US	35.8	14.2	12.7	2.3	11.1	17.5	
1/8	1/2	K2M8-US	42.2	19.1	12.7	2.3	11.1	22.2	
3/16	1/16	K3M1-US	31.2	9.7	13.7	2.3	12.7	11.1	
3/16	1/8	K3M2-US	31.2	9.7	13.7	3.0	12.7	11.1	
3/16	1/4	K3M4-US	36.3	14.2	13.7	3.0	12.7	14.3	
1/4	1/16	K4M1-US	32.8	9.7	15.2	3.0	14.3	12.7	
1/4	1/8	K4M2-US	32.8	9.7	15.2	4.8	14.3	12.7	
1/4	1/4	K4M4-US	37.8	14.2	15.2	4.8	14.3	14.3	
1/4	3/8	K4M6-US	38.4	14.2	15.2	4.8	14.3	17.5	
1/4	1/2	K4M8-US	44.7	19.1	15.2	4.8	14.3	22.2	
1/4	3/4	K4M12-US	46.2	19.1	15.2	4.8	14.3	27.0	
5/16	1/8	K5M2-US	34.0	9.7	16.3	4.8	15.9	14.3	
5/16	1/4	K5M4-US	38.6	9.7	16.3	6.4	15.9	14.3	
5/16	3/8	K5M6-US	39.1	14.2	16.3	6.4	15.9	17.5	
5/16	1/2	K5M8-US	45.5	19.1	16.3	6.4	15.9	22.2	
3/8	1/8	K6M2-US	35.3	9.7	16.8	4.8	17.5	15.9	
3/8	1/4	K6M4-US	39.9	14.2	16.8	7.1	17.5	15.9	
3/8	3/8	K6M6-US	39.9	14.2	16.8	7.1	17.5	17.5	
3/8	1/2	K6M8-US	46.2	19.1	16.8	7.1	17.5	22.2	
3/8	3/4	K6M12-US	47.8	19.1	16.8	7.1	17.5	27.0	
3/8	1	K6M16-US	47.0	23.9	16.8	7.1	17.5	34.9	
1/2	1/8	K8M2-US	38.9	9.7	22.9	4.8	22.2	20.6	
1/2	1/4	K8M4-US	43.4	14.2	22.9	7.1	22.2	20.6	
1/2	3/8	K8M6-US	43.4	14.2	22.9	9.7	22.2	20.6	
1/2	1/2	K8M8-US	49.0	19.1	22.9	10.4	22.2	22.2	
1/2	3/4	K8M12-US	50.5	19.1	22.9	10.4	22.2	27.0	
1/2	1	K8M16-US	57.2	23.9	22.9	10.4	22.2	34.9	
5/8	1/4	K10M4-US	44.2	14.2	24.4	7.1	25.4	23.8	
5/8	3/8	K10M6-US	44.2	14.2	24.4	9.7	25.4	23.8	
5/8	1/2	K10M8-US	49.0	19.1	24.4	11.9	25.4	23.8	
5/8	3/4	K10M12-US	50.5	19.1	24.4	12.7	25.4	27.0	
3/4	3/8	K12M6-US	45.7	14.2	24.4	10.4	28.6	27.0	
3/4	1/2	K12M8-US	50.5	19.1	24.4	11.9	28.6	27.0	
3/4	3/4	K12M12-US	50.5	19.1	24.4	15.7	28.6	27.0	
3/4	1	K12M16-US	57.2	23.9	24.4	15.7	28.6	34.9	
7/8	1/2	K14M8-US	50.5	19.1	25.9	11.9	31.8	30.2	
7/8	3/4	K14M12-US	50.5	19.1	25.9	15.7	31.8	30.2	
7/8	1	K14M16-US	57.2	23.9	25.9	18.3	31.8	34.9	
1	1/2	K16M8-US	57.4	19.1	31.2	11.9	38.1	34.9	
1	3/4	K16M12-US	57.4	19.1	31.2	15.7	38.1	34.9	
1	1	K16M16-US	62.2	23.9	31.2	22.4	38.1	34.9	
1 1/8	1	K18M16-US	62.2	23.9	31.2	22.4	46.0	41.3	
1 1/4	1	K20M16-US	77.2	23.9	41.1	22.4	47.6	44.5	
1 1/4	1 1/4	K20M20-US	77.2	23.9	41.1	27.7	47.6	44.5	
1 1/2	1 1/2	K24M24-US	88.9	26.2	50.0	34.0	57.2	54.0	

双卡套外螺纹直通接头



公制双卡套外螺纹直通接头			NPT 螺纹						
T-Tube O.D. (in.)	NPT 尺寸	基本订购信息	尺寸 mm						
			L	B	C	E	G	F	
2	1/8	K02M2-US	30.5	9.7	12.9	1.7	12	12	
3	1/8	K03M2-US	30.5	9.7	12.9	2.4	12	12	
3	1/4	K03M4-US	35.6	14.2	12.9	2.4	12	14	
4	1/8	K04M2-US	31.2	9.7	13.7	2.4	12	12	
4	1/4	K04M4-US	36.3	14.2	13.7	2.4	12	14	
6	1/8	K06M2-US	32.8	9.7	15.3	4.8	14	14	
6	1/4	K06M4-US	37.9	14.2	15.3	4.8	14	14	
6	3/8	K06M6-US	38.4	14.2	15.3	4.8	14	18	
6	1/2	K06M8-US	44.7	19.1	15.3	4.8	14	22	
8	1/8	K08M2-US	34.2	9.7	16.2	4.8	16	15	
8	1/4	K08M4-US	38.7	14.2	16.2	6.4	16	15	
8	3/8	K08M6-US	39.3	14.2	16.2	6.4	16	18	
8	1/2	K08M8-US	45.6	19.1	16.2	6.4	16	22	
10	1/8	K010M2-US	36.3	9.7	17.2	4.8	19	18	
10	1/4	K010M4-US	40.9	14.2	17.2	7.1	19	18	
10	3/8	K010M6-US	40.9	14.2	17.2	7.9	19	18	
10	1/2	K010M8-US	46.5	19.1	17.2	7.9	19	22	
10	3/4	K010M12-US	48.0	19.1	17.2	7.9	19	27	
10	1	K010M16-US	54.6	23.9	17.2	7.9	19	35	
12	1/8	K012M2-US	38.8	9.7	22.8	4.8	22	22	
12	1/4	K012M4-US	43.4	14.2	22.8	7.1	22	22	
12	3/8	K012M6-US	43.4	14.2	22.8	9.5	22	22	
12	1/2	K012M8-US	49.0	19.1	22.8	9.5	22	22	
12	3/4	K012M12-US	50.5	19.1	22.8	9.5	22	27	
14	1/8	K014M2-US	38.8	9.7	24.4	4.8	25	24	
14	1/4	K014M4-US	44.1	14.2	24.4	7.1	25	24	
14	3/8	K014M6-US	44.1	14.2	24.4	9.5	25	24	
14	1/2	K014M8-US	49.0	19.1	24.4	11.1	25	24	
14	3/4	K014M12-US	50.5	19.1	24.4	11.1	25	27	
15	1/2	K015M8-US	49.0	19.1	24.4	11.9	25	24	
15	3/4	K015M12-US	50.5	19.1	24.4	11.9	25	27	
15	1	K015M16-US	57.1	23.9	24.4	11.9	25	35	
16	1/4	K016M4-US	44.1	14.2	24.4	7.1	25	24	
16	3/8	K016M6-US	44.1	14.2	24.4	9.5	25	24	
16	1/2	K016M8-US	49.0	19.1	24.4	11.9	25	24	
16	3/4	K016M12-US	50.5	19.1	24.4	12.7	25	27	
18	3/8	K018M6-US	45.6	14.2	24.4	9.5	30	27	
18	1/2	K018M8-US	50.5	19.1	24.4	11.9	30	27	
18	3/4	K018M12-US	50.5	19.1	24.4	15.1	30	27	
20	1/2	K020M8-US	52.3	19.1	26.0	11.9	32	30	
20	3/4	K020M12-US	52.3	19.1	26.0	15.9	32	30	
20	1	K020M16-US	57.1	23.9	26.0	15.9	32	35	
22	1/2	K022M8-US	52.3	19.1	26.0	11.9	32	30	
22	3/4	K022M12-US	52.3	19.1	26.0	15.9	32	30	
22	1	K022M16-US	57.1	23.9	26.0	18.3	32	35	
25	1/2	K025M8-US	57.5	19.1	31.3	11.9	38	35	
25	3/4	K025M12-US	57.5	19.1	31.3	15.9	38	35	
25	1	K025M16-US	62.3	23.9	31.3	21.8	38	35	
28	1	K028M16-US	72.4	23.9	36.6	21.8	46	41	
28	1 1/4	K028M20-US	73.1	23.9	36.6	21.8	46	46	
30	1 1/4	K030M20-US	77.2	23.9	39.6	26.2	50	46	
32	1 1/4	K032M20-US	79.6	23.9	42.0	28.6	50	46	
38	1 1/2	K038M24-US	91.6	26.2	49.4	33.7	60	55	

## 双卡套内螺纹直通接头



英制双卡套内螺纹直通接头			NPT 螺纹						
T-Tube O. D. (mm)	NPT 尺寸	基本订购信息	尺寸mm						
			L	B	C	E	G	F	
1/16	1/16	K1F1-US	23.6	9.9	8.6	1.3	7.9	11.1	
1/16	1/8	K1F2-US	24.4	10.4	8.6	1.3	7.9	14.3	
1/8	1/8	K2F2-US	28.7	10.4	12.7	2.3	11.1	14.3	
1/8	1/4	K2F4-US	33.5	15.0	12.7	2.3	11.1	19.1	
3/16	1/8	K3F2-US	29.7	10.4	13.7	3.0	12.7	14.3	
1/4	1/8	K4F2-US	31.2	10.4	15.2	4.8	14.3	14.3	
1/4	1/4	K4F4-US	35.8	15.0	15.2	4.8	14.3	19.1	
1/4	3/8	K4F6-US	37.6	15.0	15.2	4.8	14.3	22.2	
1/4	1/2	K4F8-US	42.4	19.8	15.2	4.8	14.3	27.0	
5/16	1/8	K5F2-US	32.0	10.4	16.3	6.4	15.9	14.3	
5/16	1/4	K5F4-US	36.8	15.0	16.3	6.4	15.9	19.1	
3/8	1/8	K6F2-US	32.8	10.4	16.8	7.1	17.5	15.9	
3/8	1/4	K6F4-US	37.6	15.0	16.8	7.1	17.5	19.1	
3/8	3/8	K6F6-US	39.1	15.0	16.8	7.1	17.5	22.2	
3/8	1/2	K6F8-US	43.9	19.8	16.8	7.1	17.5	27.0	
3/8	3/4	K6F12-US	47.8	20.6	16.8	7.1	17.5	33.3	
1/2	1/4	K8F4-US	40.4	15.0	22.9	10.4	22.2	20.6	
1/2	3/8	K8F6-US	41.9	15.0	22.9	10.4	22.2	22.2	
1/2	1/2	K8F8-US	46.7	19.8	22.9	10.4	22.2	27.0	
1/2	3/4	K8F12-US	48.3	20.6	22.9	10.4	22.2	33.3	
5/8	3/8	K10F6-US	41.9	15.0	24.4	12.7	25.4	23.8	
5/8	1/2	K10F8-US	46.7	19.8	24.4	12.7	25.4	27.0	
3/4	1/2	K12F8-US	46.7	19.8	24.4	15.7	28.6	27.0	
3/4	3/4	K12F12-US	48.3	20.6	24.4	15.7	28.6	33.3	
7/8	3/4	K14F12-US	49.8	20.6	25.9	18.3	31.8	33.3	
1	3/4	K16F12-US	53.3	20.6	31.2	22.4	38.1	34.9	
1	1	K16F16-US	62.2	25.4	31.2	22.4	38.1	41.3	
1 1/4	1 1/4	K20F20-US	74.7	25.4	41.1	27.7	47.6	54.0	
1 1/2	1 1/2	K24F24-US	83.3	27.7	50.0	36.3	57.2	60.3	